

## **Features**



Today's Lifestyle Shower 3

**Quiet Operation** 



Splash Proof Casing



Double Relay ELCB



Energy Saving Inverter DC Pump



Available in Delightful Colour Choices



Easy Clean Durable Nozz

ELCB Test/Reset & Purnp Buttons



Easy to Operate



Flow Rate: Up to 400%



Thermal Safety Cut-Off 🔀

Easy to Install

<sup>1</sup>For iSENSE ESP only

## <sup>2</sup>For iSENSE EP and ESP only

## **Specifications**

>	Innovative	Features	<b>ISENSE</b>		ESP		<b>ISENSE</b>
■ Double relay self test ELĈB							
_ Quiet DC k	ooster pump	1					
AC booste		-		-			
Standard	_						
Auto flow s	sensor switch						
Safety anti	-scalding devic	e e					
Stop valve	•	1					
Rain show	er	-		-			
3-way mas	sage spray ha	nd shower					
Electronic	touch power se	election					
Sleek and	slim design	1					
Leak proof	heater tank	1					
■ Splash pro	of casing IP25	1					
■ Built-in EL	CB with surge	brotector					
<sub>-</sub> 5 years wa	arranty ( Invert <b>ě</b>	r DC pump )					
_ Up to 400%	% stronger wat	er flow rate					
_ 60% powe	r saving pump	1					
Specificat	ions						
Power ratii	ng (kW)	3.7		3.7			
Voltage (V	)	240		240			
Frequency		50		50			
Minimum v	vater pressure	(kgf/cm²)		0.14		0.14	
(psi)		2		2			
Maximum water pressure(kgf/cm²)				3.87		3.87	
(psi)		55		55			
Water con	nection	(mm)		15		15	

(inches) Water temperature co	1/2 BSP	1/2 BSP				
touch						
panel						
selection	Electronic					
touch						
panel						
selection						
Pump rating	48 (24V d.c.)	-				
Product Dimensions						
Depth (mm)	100	100				
Width (mm)	240	240				
Height	390	390				
Weight (kg)	3.4	3.0				

