



## Features




Splash Proof Casing IP25



Double Relay ELCB



Easy Clean Durable Nozzl 

ELCB Test Button



Thermal Safety Cut-Off 

Easy to Install

## Specifications

**Innovative Features** 119**E**Double relay ELCB 

Quiet DC booster pump -

AC booster pump -

**Standard Features**Auto flow sensor switch Thermal safety cut-off 3 in 1 stop valve 3-way massage spray hand shower Stepless electronic power  controlSleek and slim design Leak proof heater tank Splash proof casing IP25 

Up to 400% stronger water flow rate

60% power saving pump -

**Specifications**

Power rating (kW) 3.7

Voltage (V) 240

Frequency (Hz) 50

Minimum water pressure (kgf/cm<sup>2</sup>) 0.14  
(psi) 2Maximum water pressure(kgf/cm<sup>2</sup>) 3.87  
(psi) 55Water connection (mm) 15  
(inches) 1/2 BSP

Water temperature controlVariable

stepless

electronic

control

Pump rating -

**Product Dimensions**

Depth (mm) 95

Width (mm) 210

Height 310

Weight (kg) 3



Industry Excellence Award  
2002 & 2006



Malaysia Good Design



Suruhanjaya Tenaga



MS  
FD001101



Ruhan Merdeka